

CAUTION: *Open Slowly! Contents are under pressure.*

SEALER STRIPPER

PURPOSE: To remove sealer, paint, and any type of coating from concrete surfaces without harming concrete. STRIPPER works on acrylic, varnish, latex, lacquer, urethane, epoxy and most any type of coating.

APPLICATION: Test a small area for results before application. Roll Stripper on concrete. Allow to sit for 10 minutes. If exterior, Power Wash residue away with water. For interior, use a scrub brush and a flat blade. Do small areas of no more than 100 square feet at a time. Stubborn coatings will require multiple applications of stripper. Clean with CLEANER DEGREASER and rinse with clean water.

NOTE: Timing is critical. Watch for film to lift. Removing too soon will leave coating. If left too long, coating will dry and re-seal.

RATE: Use as approximately as many gallons of STRIPPER as gallon of sealer that were applied. If coatings are unknown use approximately 100 -200 square feet per gallon.

CAUTION: Use safety glasses, rubber gloves, and respirator. Clothe all areas of your body. Avoid breathing vapors. Pre-soak with water and cover any plants that may come in contact with stripper or its residue.

STORAGE: Store in cool shaded area. STRIPPER will develop unsafe pressure in hot areas and will boil at 105°F

FIRST AID: If any of the following conditions persist, contact medical personnel immediately.

- INHALATION: If breathing becomes labored, move to fresh air.
- EYE CONTACT: If eyes are contacted, immediately flush with water.
- SKIN CONTACT: Product is irritating to skin. If contact occurs wash with water and mild soap.
- INGESTION: Contact Physician, Poison Control, or Hospital Emergency Room immediately.

NFPA/HMIS

Health	2	Moderate
Flammability	1	Slight
Reactivity	1	Slight
Protection	I	Use Glasses, Gloves, & Respirator

Active Ingredients:

Methylene Chloride CAS# 75-09-02
Methanol CAS # 67-56-1

D.O.T. Info: UN1280, Toxic Liquids, Organic, N.O.S. (Dichloromethane, Methanol), 6.1, PGIII
Emergency Contact: INFOTRAC 1-800-535-5035

Made in USA

Clemons Concrete Coatings

★505 Cave Rd. Nashville, TN 37210 ★ www.ccc-usa.com★