

# A100 -SOLVENT

## PURPOSE & APPLICATION:

- 1) Allow moisture to release from sealed concrete. Roll, brush, or spray on to surface of solvent based acrylic sealer. Sealer will dry hard again within a few hours. Allow 4 hours to dry before walking on and 48 hours before driving on surface.
- 2) Dissolve bubbles in film by re-emulsifying sealer.
- 3) Clean up of tools. Soak metal tools briefly, wipe clean, and allow to dry.
- 4) Thinner for sealer. Solvent will thin solvent based acrylic sealer. Add Sealer to solvent 4:1 and stir for a minute.

**CAUTION:** Flammable! Contains Petroleum distillates. Keep away from heat and flames. Use only with adequate ventilation. Avoid prolonged breathing of vapors and contact with skin. Keep out of eyes and mouth. **WEAR RUBBER GLOVES AND SAFETY GLASSES.** Keep container closed when not in use. In case of spill, absorb and dispose of in accordance with local applicable regulations. **KEEP AWAY FROM CHILDREN!**

## FIRST AID:

- Skin Contact: Flush with water. Remove contaminated clothing.
- Eye Contact: Flush with water for 15 minutes.
- Inhalation: Move to fresh air.
- Ingestion: Do not induce vomiting. Keep at rest. Seek medical attention immediately. If dizziness occurs remove to fresh air and seek medical attention.

## HMIS RATING

Health	2	Moderate
Flammability	3	Serious
Reactivity	0	Minimal
Protection	B	Wear Glasses and Gloves

**INGREDIENTS:** CAS # 64742-95-6 AROMATIC HYDROCARBON  
CAS # 108-88-3 TOLUENE  
CAS # 8052-41-3 ALIPHATIC NAPHTHA

DOT Information: PAINT RELATED MATERIALS / 3 / UN1263 / PG III

**Made in USA**

Clemons Concrete Coatings

★505 Cave Rd. Nashville, TN 37210 ★ www.ccc-usa.com★(615) 872-9099★