

USES

Pavers, concrete and retaining walls. Can also be used on manufactured and natural stone, tile, terrazzo and stucco on both horizontal and vertical applications.

RELATED PRODUCTS

SB-488 Efflorescence & Rust Remover
SB-1300 Joint Stabilizing Sealer
SB-600 Wet Look Sealer
SB-4000 Water Repelling Invisible Sealer
SB-5000 Stainblocking Invisible Sealer
SB-7000 Concrete Sealer
SB-10 Paver Bond®

PRODUCT DESCRIPTION

SB-442 General Stain Remover is a concentrated, non-acid degreaser and general purpose cleaner for use on pavers, concrete and retaining walls. This technologically advanced cleaner removes motor oil, food and beverage stains. It is environmentally friendly and replaces several types of harsh acid cleaners. SB-442 General Stain Remover's unique Clean Rinse Technology lifting power allows residue to be quickly and easily rinsed away with a high or low pressure water sprayer. SB-442 General Stain Remover's chemical blend draws out stains from within the surface but does not etch or damage concrete, anodized aluminum or painted surfaces. The product can be used to clean and maintain Surebond sealed pavements as it is compatible with all other Surebond products. It is suitable for both horizontal and vertical surfaces. Phosphate free.

| Features | Benefits |
|--|---|
| What makes SB-442 General Stain Remover different? | |
| Powerful | • Cleans oil, dirt and grease |
| Safe | • Does not damage or etch surfaces and building materials |
| Environmentally friendly | • Biodegradable and replaces harsh, acid-based cleaners |
| Clean Rinse Technology | • Does not leave cleaner residue on the surface |
| Compatible | • Works with all Surebond sealers |
| Versatile | • Works on both horizontal and vertical surfaces |

PREPARATION

To determine the suitability of this product for a specific surface, test on a small, inconspicuous area first. Inspect area for visible staining to determine stain types and quantity. Sweep and remove all soil and other debris from the surface.

APPLICATION INFORMATION

Pre-treat and saturate stained area while dry to increase degreaser effectiveness and to ensure penetration into the textured surface. Add 8 to 16 ounces of concentrate for each gallon of water used, depending on the severity of the stain. Apply using a garden sprayer, low pressure siphon or bulk sprayer. Allow cleaner to soak into the surface for 5 to 10 minutes. Improve results by scrubbing surface with a natural fiber brush to agitate and break down stains. Use a high pressure, hot water wash to draw out and further break down surface stains. Rinse surface thoroughly. It may be necessary to use stronger concentrations and secondary cleanings to remove heavier, deep set stains.



MAINTENANCE

Pavement and wall maintenance should be carried out per instructions on appropriate sealer data sheet. Surebond cleaners are compatible with all Surebond sealers.

PACKAGING/SIZES

4 x 1 gallon containers per case
5 gallon pails
55 gallon drums
Bulk packaging available

COVERAGE*

| MATERIAL | SQ FEET | SQ METER |
|--------------|-----------|-------------|
| All Surfaces | 400 – 800 | 37.2 - 74.4 |

*Per gallon. Coverage based on single treatment. Some applications may require additional treatments. Actual coverage may vary depending on the type, age, condition and porosity of the surface, application method and other local conditions.

STORAGE

Store in a cool place and protect from freezing.

SHELF LIFE

Two years when properly stored.

PRECAUTIONARY INFORMATION

Eye and skin irritant. Contains Alkaline Silicates, Surfactants and Glycol Ether Solvents. Do not get in eyes, on skin or clothing. Harmful if swallowed. Do not take internally.

FIRST AID: For eyes, flush immediately with plenty of water for at least 15 minutes and get medical attention. For skin, wash thoroughly with water. If irritation persists, see a doctor. If swallowed, drink large quantities of water or milk. Get medical attention immediately. Keep out of reach of children (see Material Safety Data Sheet).

LIMITATIONS

Avoid contact with glass. If this product is allowed to dry on glass a residue may be created which is not removable. If accidentally splashed on glass, flush immediately with water. Do not expose containers to freezing temperatures and store inside during cold weather. Test cleaning is always recommended to ensure both the proper physical and aesthetic properties prior to starting a project.

WARRANTY

Manufacturer warrants its products conform to the published specifications. No other warranties are expressed or implied, including those of merchantability or fitness or any purpose not expressly set forth herein. The user must determine suitability of the products for their particular use. Manufacturer and any seller's liability for incidental or consequential damage hereunder shall not exceed the purchase price of the product used.

ASSISTANCE & ADDITIONAL INFORMATION

For sales, specification assistance, technical questions, detailing, etc., please contact:

SUREBOND

2801 International Lane

Madison, WI 53704 USA

Toll Free (US & Canada): 888-44SURE1 (888-447-8731)

Phone: (608) 237-7554

Fax: (608) 237-7558

Email: info@surebond.com