

# SUPER SEAL - A

## Urethane Modified Water-borne Acrylic CONCRETE SEALER

### **DESCRIPTION:**

- 25% solids
- Seals and protects
- Resists hot tire pickup
- Urethane modified for increased abrasion resistance
- Non-yellowing protection from the sun
- Water-based, non-flammable, & environmentally friendly
- Easy to apply & cleanup with water

**SURFACE PREPARATION:** Surface must be clean & dry. Scrub oil spots with concrete cleaner. We recommend CLEANER DEGREASER. For smooth troweled concrete use ETCH & CLEAN. Pressure-wash with water at 3000 psi or more. Allow at least 24 hours to dry. Surface must be free of other coatings, waxes, and paint. Always test a small area to your satisfaction before proceeding.

**APPLICATION:** Apply at substrate temperatures above 50° F. Apply with sprayer. For exterior concrete, you may use a medium nap roller. For smooth concrete you may use a lamb's wool applicator or short nap roller and cross roll. Thoroughly saturate surface. Apply at approximately 200 ft<sup>2</sup> per gallon on brushed concrete and 300 ft<sup>2</sup> per gallon on smooth-troweled concrete. That may vary due to roughness and porosity of surface. Apply additional coats as needed for increased gloss.

**DRYING TIME:** Allow 4 hours for foot traffic, 72 hours for auto traffic. Do not apply if rain is imminent.

**CLEAN UP:** Wash with water.

**NOTE:** Keep from freezing. Store between 40° and 100° F.

**CAUTION:** Use with adequate ventilation. Avoid direct contact. Symptoms of exposure are redness and irritation to skin and burning and blurred vision to eyes.

### **FIRST AID:**

- \* EYES-Flush thoroughly for 15 minutes. Seek medical attention.
- \* SKIN-Wash with soap & water. If irritation persists, seek medical attention.
- \* INTERNAL- Do not induce vomiting. Call a doctor or poison control immediately.
- \* INHALATION-Move to fresh air. Consult doctor if breathing difficulty persists.
- \* SKIN ABSORPTION-No harmful results expected.

### **INGREDIENTS:**

Acrylic  
Urethane  
Water  
Dipropylene glycol n-butyl ether  
Dipropylene glycol monomethyl ether

### **CAS#**

Trade Secret  
Trade Secret  
732-18-5  
29911-28-2  
34590-94-8

### **DOT INFORMATION:**

Non-Regulated Material  
Made in USA

Clemons Concrete Coatings

★505 Cave Rd. Nashville, TN 37210 ★ [www.ccc-usa.com](http://www.ccc-usa.com)★(615) 872-9099★